

COMMUNICATION APPARATUS, COMMUNICATION SYSTEM
AND METHOD FOR INTEGRATING SPEECH AND DATA

BACKGROUND OF THE INVENTION

5

(1) Field of the Invention

This invention relates to a communication apparatus,
communication system, and method for integrating speech and
data and, more particularly, to a communication apparatus
10 for communicating by integrating speech and data,
communication system for communicating by integrating
speech and data, and method for integrating speech and data
for communicating by integrating and controlling speech and
data.

15 (2) Description of the Related Art

In recent years, in addition to conventional
centralized telephone switching service, the use of high-
speed transmission via distributed LAN for local
communication is increasing. As a result, intranet
20 communication is widely performed. Conventionally,
installations for such an in-house PBX network and intranet
have been constructed separately from each other because of
their difference in protocol. Conventionally, a public
telephone trunk network and internet trunk network have
25 also been installed separately from each other.

A telephone network and data network are installed
separately from each other in this way, resulting in low

installation efficiency. Furthermore, lines are used separately, resulting in low efficiency in the use of lines.

To take an example of conventional techniques, Japanese Patent Laid-Open Publication No.Hei11-252249
5 discloses a switching system for exchanging frames, being speech made into MAC frames, and LAN data in order to realize communication in which telephone speech and data are integrated.

In recent years, on the other hand, Internet
10 telephone for performing speech communication via Internet has appeared. It uses voice over IP (VoIP) technique in order to realize speech communication on an IP network.

The above conventional technique, however, needs to develop a new switching system which accommodates trunk
15 lines for telephones, data terminals, public networks, etc. Therefore, it is not easy to change the installations.

Communication networks are built with telephone networks as their centers. Therefore, what is important is not to simply add new systems, but to minimize the increase
20 of installations by the use of the existing network systems in order to provide new services.

The conventional Internet telephone must be connected to a dedicated server in order to speak. Moreover, the inability to ensure bandwidth for the
25 conventional Internet telephone causes delay or lack of speech, resulting in poor speech communication quality.

SUMMARY OF THE INVENTION

An object of the present invention is to provide a communication apparatus for performing high-quality communication by integrating speech and data efficiently.

5 Another object of the present invention is to provide a communication system for performing high-quality communication by integrating speech and data efficiently.

Still another object of the present invention is to provide a method for integrating speech and data for
10 performing high-quality communication by integrating speech and data efficiently.

In order to achieve the above object, a communication apparatus for communicating speech and data is provided. This communication apparatus comprises frame
15 controlling means for integrating speech frames, being speech signals made into frames, and data frames, being data made into frames, into integrated frames and controlling the routing of the speech frames, the data frames, and the integrated frames, input processing means
20 for storing and managing at least one of the three types of frames of the speech frames, the data frames, and the integrated frames, and output processing means for storing and managing the frames transferred, setting a bandwidth ratio of the frames dynamically, and transmitting the
25 speech frames, the data frames, and the integrated frames from on lines.

Furthermore, in order to achieve the above object,

a communication system for communicating speech and data is provided. This communication system comprises a telephone switching system, a network connecting device for performing a connecting process between networks, and a
5 communication apparatus comprising frame controlling means for integrating speech frames, being speech signals made into frames, and data frames, data made into frames, into integrated frames and controlling the routing of the speech frames, the data frames, and the integrated frames, input
10 processing means for storing and managing at least one of the three types of frames of the speech frames, the data frames, and the integrated frames, and output processing means for storing and managing the frames transferred, setting a bandwidth ratio of the frames dynamically, and
15 transmitting the speech frames, the data frames, and the integrated frames from on lines and connected to at least one of an office telephone interface line of the telephone switching system, an office data interface line of the network connecting device, and an interoffice trunk line.

20 Moreover, in order to achieve the above object, a method for integrating speech and data for communicating by integrating and controlling speech and data is provided. This method for integrating speech and data comprises the
25 step of integrating speech frames, being speech signals made into frames, and data frames, being data made into frames, into integrated frames, the step as an input-side process of storing and managing at least one of the three

types of frames of the speech frames, the data frames, and the integrated frames, the step of controlling the routing of the speech frames, the data frames, and the integrated frames, and the step as an output-side process of storing and managing the frames transferred, setting a bandwidth ratio of the frames dynamically, and transmitting the speech frames, the data frames, and the integrated frames from on lines.

The above and other objects, features and advantages of the present invention will become apparent from the following description when taken in conjunction with the accompanying drawings which illustrate preferred embodiments of the present invention by way of example.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a view for describing the principle of a communication apparatus according to the present invention.

Fig. 2 is a view showing the configuration of a communication system.

Fig. 3 is a view showing a model for network configuration.

Fig. 4 are views showing the structure of frames.

Fig. 5 is a view showing the structure of an integrated frame in detail.

Fig. 6 is a schematic showing a process for transferring frames.

Fig. 7 is a view showing the configuration of a

communication apparatus.

Fig. 8 is a view showing the configuration of a communication apparatus.

Fig. 9 is a view roughly showing a process performed when identical IP frames exist.

Fig. 10 is a flow chart showing the procedure of processes performed in a method for integrating speech and data according to the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENT

An embodiment of the present invention will now be described with reference to the drawings. Fig. 1 is a view for describing the principle of a communication apparatus according to the present invention. A communication apparatus 10 communicates speech and data. In the present invention, speech means a speech signal on a telephone line and data means Internet protocol (IP) data.

Frame controlling means 12 integrates speech frames, being speech signals made into frames, and data frames, data made into frames, into integrated frames and controls the routing of speech frames, data frames, and integrated frames.

Input processing means 11 stores and manages at least one type of speech frames, data frames, and integrated frames. In Fig. 1 speech and data frames are input. However, if the communication apparatus 10 connects with another communication apparatus and this communication apparatus sends integrated frames, they will also be input

to the input processing means 11.

Output processing means 13 stores and manages these frames transferred. In addition, it sets a bandwidth ratio of frames dynamically and transmits speech frames, data frames, and integrated frames from on lines.

In Fig. 1, speech frame bandwidth is assigned to line L1 and speech frames are transmitted via line L1; data frame bandwidth is assigned to line L2 and data frames are transmitted via line L2.

Moreover, integrated frame bandwidth is assigned to line L3 and integrated frames are transmitted via line L3. That is to say, signals in which speech and data mix are transmitted via line L3.

There is little telephone traffic at night-time. In this case the output processing means 13 can assign data frame bandwidth dynamically to, for example, line L1 to which speech frame bandwidth is assigned in the daytime. Volumes of data can be transferred in this way, which enables flexible transmission control.

A communication system according to the present invention in which the communication apparatus 10 is applied will now be described. Fig. 2 is a view showing the configuration of a communication system. A communication system 10a comprises a telephone switching system 102, a network connecting device 105 (router 105 in Fig. 2) corresponding to a router or gateway, and the communication apparatus 10.

The communication apparatus 10 is connected to at least one of office telephone interface line If1 of the telephone switching system 102, office data interface line If2 of the router 105, and interoffice trunk lines L1 through L3.

With the communication system 10a, a subscriber terminal 2 corresponding to a telephone, personal computer, or the like is connected to the telephone switching system 102 and an asymmetric digital subscriber line (ADSL) modem 103 via a main distributing frame (MDF) 101 in a station 100.

The MDF 101 is a distributing frame for accommodating and distributing communication cables. The ADSL modem 103 is one for performing high-speed digital communication by the use of a telephone line.

A trunk 104 connects with the telephone switching system 102 and the communication apparatus 10 and controls an interface for speech signals. The router 105 connects with the ADSL modem 103, the communication apparatus 10, and a server 106 and controls an interface for IP packets.

The station 100 connects with stations 311 through 313 via interoffice trunk lines L1 through L3 respectively. The communication apparatus 10 in the station 100 connects with a communication apparatus 10-1 in the station 311 via speech interface (TEL) line L1.

The communication apparatus 10 in the station 100 connects with a communication apparatus 10-2 in the station

312 via data interface (IP) line L2; the communication apparatus 10 in the station 100 connects with a communication apparatus 10-3 in the station 313 via integrated interface (Telephone IP: TIP) line L3.

5 In this case, for example, office telephone interface line If1 and office data interface line If2 each accommodate 622-Mbps OC12/STM-4 interface.

 Speech interface line L1 accommodates 156-Mbps OC3/STM-1 interface; data interface line L2 and integrated
10 interface line L3 each accommodate 622-Mbps OC12/STM-4 interface.

 Fig. 3 is a view showing a model for network configuration. In Fig. 3, black circles indicate stations having a local switch (LS) and black squares indicate
15 stations having a toll switch (TS). Furthermore, all stations include the communication apparatus 10 according to the present invention.

 Stations 121-125 at LS stage are exchanges for accommodating subscribers, have a double loop configuration
20 (currently-used/spare connection configuration), and connect with subscriber terminals 2a-2e respectively.

 Stations 131-134 at TS stage are exchanges having a relay function and have a double loop configuration. The stations 131 and 132 each connect with the stations 121-125.
25 A regional center 135 is an exchange for managing stations in an network and connects with the stations 131-134.

 Now, the structure of frames output from the

communication apparatus 10 will be described. Fig. 4 are views showing the structure of frames. Figs. 4(A), 4(B), and 4(C) indicate the structure of integrated frame F2 on integrated interface line L3, speech frame F3 on speech interface line L1, and data frame (IP frame) F4 on data interface line L2 respectively.

Integrated frame F2 shown in Fig. 4(A) consists of a header 21, a speech frame 22, and an IP frame 23. In integrated frame F2, bandwidth used actually for a telephone line is occupied by the speech frame 22 and the rest of the bandwidth is assigned to the IP frame 23.

In addition, the IP frame 23 consists of, for example, three IP packets in one cycle and QOS priority for each packet is set. This priority information is set in the header 21 (described later in Fig. 5).

Speech frame F3 shown in Fig. 4(B) is a frame signal generated by making telephone speech into a frame. IP frame F4 shown in Fig. 4(C) consists of a plurality of IP packets.

Now, the structure of integrated frame F2 will be described in detail. Fig. 5 is a view showing the structure of integrated frame F2 in detail. Integrated frame F2 consists of the header (HD) 21, the speech frame (TS0 and TS1) 22, the IP frame (IP0, IP1, and IP2) 23, and a tail (TL) 24 with CRC indicating the tail of a frame.

In this case, TS0 is a speech frame for an upper telephone line and TS1 is a speech frame for an ordinary

telephone line. IPn (IP0 through IP2) is an IP packet frame with priority "n." For example, priority "0" corresponds to bandwidth-guaranteed connection-mode communication and priority "1" and "2" correspond to non-
5 bandwidth-guaranteed connectionless-mode communication (best-effort etc.).

In the header 21, SYNC is a synchronizing pattern; PLL is payload length; HDL is header length; CCS is a control field for No. 7 common line signaling system for
10 telephone and IP. CCS enables to ensure bandwidth for control signals for speech and IP and to transmit them without being influenced by traffic.

TS-IDX is a telephone frame index. TS0-Slot-IDX is an upper telephone slot-state index. For example, "00,"
15 "01," "10," and "11" indicate "inactive/shut down," "inactive/shut down for maintenance," "active and unused," and "active and used" respectively. TS1-Slot-IDX is an ordinary telephone slot-state index. For example, "00," "01," "10," and "11" indicate "inactive/shut down,"
20 "inactive/shut down for maintenance," "active and unused," and "active and used" respectively.

IP-IDX and IPn-IDX correspond to priority information fields. IP-IDX is an IP frame index; IPn-IDX is an nth-priority IP packet index. HD-CRC is header CRC.

25 As described above, the communication apparatus 10 according to the present invention controls the routing of speech frames, IP frames, and integrated frames, and

transmits speech frames, IP frames, and integrated frames via speech interface line L1, data interface line L2, and integrated interface line L3 respectively.

Furthermore, speech frames are guaranteed bandwidth which they use, and the transmission of IP frames is controlled on the basis of priority as a semi-bandwidth guarantee.

This improves speech communication quality by comparison with conventional Internet telephone and enables to communicate by integrating speech and IP frames.

Moreover, by configuring the communication system 10a according to the present invention by connecting the communication apparatus 10 according to the present invention to office telephone interface line If1, office data interface line If2, and interoffice trunk lines, speech communication, data communication, and speech-data communication in which speech and data are integrated can be performed easily. In addition, by making good use of the existing network systems, new services can be provided with the increase of installations minimized.

The process of transferring frames will now be described. Fig. 6 is a schematic showing a process for transferring frames. Black circles, white circles, black squares, white squares, and diamonds in Fig. 6 indicate upper speech frames, ordinary speech frames, first-priority IP frames, second-priority IP frames, and third-priority IP frames respectively.

Input processing means 11-1 which stores speech frames has a storage area consisting of A and B sides. It is assumed that A and B sides are receiving buffers 11-1a and 11-1b respectively. Furthermore, in Fig. 6 the receiving buffers 11-1a and 11-1b each have a storage area for two lines.

Similarly, input processing means 11-2 which stores IP frames consists of receiving buffers 11-2a and 11-2b and the receiving buffers 11-2a and 11-2b each have a storage area for two lines. Input processing means 11-3 which stores integrated frames consists of receiving buffers 11-3a and 11-3b and the receiving buffers 11-3a and 11-3b each have a storage area for two lines.

Sides of the above receiving buffers 11-1a through 11-3a and 11-1b through 11-3b are switched at cycles of, for example, 2 milliseconds. The cycle of each frame therefore is also 2 milliseconds.

On the other hand, output processing means 13-1 which stores and outputs speech frames transferred from the frame controlling means 12 has storage areas TEL#1 through TEL#4 for four lines. Similarly, output processing means 13-2 which stores and outputs IP frames transferred from the frame controlling means 12 has storage areas IP#1 through IP#4 for four lines; output processing means 13-3 which stores and outputs integrated frames transferred from the frame controlling means 12 has storage areas TIP#1 through TIP#4 for four lines.

IF1 through IF3 in Fig. 6 indicate the flow of frames on lines. IF1 indicates that upper speech frames and ordinary speech frames are transmitted via speech interface line L1 in that order.

5 IF2 indicates that first-priority IP frames, second-priority IP frames, and third-priority IP frames are transmitted via data interface line L2 in that order.

10 IF3 indicates that upper speech frames, ordinary speech frames, first-priority IP frames, second-priority IP frames, and third-priority IP frames are transmitted via integrated interface line L3 in that order.

The process of transferring frames is performed in the following way. Speech frames in storage area r1 of the receiving buffer 11-1a are transferred to storage area
15 TIP#1 of the output processing means 13-3 by the frame controlling means 12. IP frames in storage area r2 of the receiving buffer 11-2a are transferred to storage area TIP#1 of the output processing means 13-3.

When frames are transferred, the frame controlling
20 means 12 generates integrated frames by adding necessary header information. These integrated frames are stored in storage area TIP#1 of the output processing means 13-3.

The output processing means 13-3 then sets bandwidth dynamically with the traffic on integrated
25 interface line L3 taken into consideration and outputs the integrated frames. The process of transferring other frames is also performed in the same way, so descriptions

of them will be omitted.

Telephone switching systems and routers which have already been installed can be used for single-office telephone switching and local IP connection in order to
5 avoid centralized load processing. This will not be covered by the communication apparatus 10 according to the present invention.

Now, the configuration of the communication apparatus 10 for realizing the above process of
10 transferring frames will be described in detail. Fig. 7 is a view showing the configuration of a communication apparatus. A communication apparatus 1a consists of input processing means 11-1 through 11-n, frame controlling means 12-1, and output processing means 13-1 through 13-n.

15 In the input processing means 11-1, input interface means 111 controls an interface in order to receive input frames, being speech frames, IP frames, or integrated frames.

An input CPU 112 controls all the inside of the
20 input processing means 11-1. Input frame storing means 113 consists of two receiving buffers, as described in Fig. 6, and stores input frames. In addition, the input frame storing means 113 sends input frames to the frame controlling means 12-1 in accordance with an instruction
25 from the input CPU 112.

Direct memory access (DMA) controlling means 114 sends the frame controlling means 12-1 information

regarding input frames (including a destination and
corresponding to header information described in Fig. 5)
stored in the input frame storing means 113. The internal
configuration of the input processing means 11-2 through
5 11-n is the same as that of the input processing means 11-1,
so descriptions of them will be omitted.

In the output processing means 13-1, output
interface means 131 controls an interface in order to send
output frames, being speech frames, IP frames, or
10 integrated frames, from on a line.

An output CPU 132 controls all the inside of the
output processing means 13-1. Output frame storing means
133 stores output frames sent from the frame controlling
means 12-1. In addition, the output frame storing means
15 133 sends output frames to the output interface means 131
in accordance with an instruction from the output CPU 132.

DMA controlling means 134 sends the frame
controlling means 12-1 information regarding output frames
stored in the output frame storing means 133. The internal
20 configuration of the output processing means 13-2 through
13-n is the same as that of the output processing means 13-
1, so descriptions of them will be omitted.

The frame controlling means 12-1 consists of switch
controlling means 12a and switching means 12b. The switch
25 controlling means 12a controls the routing of frames
(controls routing in order to transfer frames from input
processing means to the corresponding output processing

means) and the switching means 12b on the basis of frame information sent from the DMA controlling means 114 and 134. The switching means 12b performs a switching transfer of frames in accordance with an instruction from the switch
5 controlling means 12a.

As described above, the frame controlling means 12-1 of the communication apparatus 1a controls routing on the basis of frame information and performs a switching transfer of frames to one of the output processing means
10 13-1 through 13-n. This enables communication in which speech and data are integrated efficiently.

A modification of the communication apparatus 1a will now be described. Fig. 8 is a view showing the configuration of a communication apparatus. A
15 communication apparatus 1b, being a modification of the communication apparatus 1a, consists of input processing means 11a-1 through 11a-n, frame controlling means 12-2, and output processing means 13a-1 through 13a-n.

In the input processing means 11a-1, the input
20 interface means 111 controls an interface in order to receive input frames, being speech frames, IP frames, or integrated frames.

The input CPU 112 controls all the inside of the input processing means 11a-1. The input frame storing
25 means 113 consists of two receiving buffers, as described in Fig. 6, and stores input frames. In addition, the input frame storing means 113 sends input frames and frame

information to frame controlling means 12-2 in accordance with an instruction from the input CPU 112. The internal configuration of the input processing means 11a-2 through 11a-n is the same as that of the input processing means 11a-1, so descriptions of them will be omitted.

In the output processing means 13a-1, the output interface means 131 controls an interface in order to send output frames, being speech frames, IP frames, or integrated frames, from on a line.

The output CPU 132 controls all the inside of the output processing means 13a-1. The output frame storing means 133 stores output frames sent from the frame controlling means 12-2. In addition, the output frame storing means 133 sends output frames to the output interface means 131 in accordance with an instruction from the output CPU 132. The internal configuration of the output processing means 13a-2 through 13a-n is the same as that of the output processing means 13a-1, so descriptions of them will be omitted.

The frame controlling means 12-2 includes transfer scheduling information generating means 200. The transfer scheduling information generating means 200 performs routing control (controls routing in order to transfer frames from input processing means to the corresponding output processing means) and generates transfer scheduling information t1 through tn regarding routes, on the basis of frame information sent from the input processing means 11a-

1 through 11a-n.

In order to transfer frames, first the input processing means 11a-1 sends the transfer scheduling information generating means 200 information regarding
5 frames stored in the input frame storing means 113.

When the transfer scheduling information generating means 200 receives the frame information, it generates transfer scheduling information t1 and returns transfer scheduling information t1 to the input processing means
10 11a-1.

The input processing means 11a-1 receives transfer scheduling information t1. Then the input processing means 11a-1 determines, from the contents of transfer scheduling information t1, the output processing means to which frames
15 stored in the input frame storing means 113 should be sent. After the determination, the input processing means 11a-1 sends them to the corresponding output processing means via the frame controlling means 12-2. A transfer of frames by the input processing means 11a-2 through 11a-n is performed
20 in the same way, so descriptions of it will be omitted.

In the communication apparatus 1b according to the present invention, as described above, the transfer scheduling information generating means 200 in the frame controlling means 12-2 generates transfer scheduling
25 information t1 through tn on the basis of frame information. Then frames are transferred from the input processing means 11a-1 through 11a-n to the corresponding output processing

means 13a-1 through 13a-n on the basis of transfer scheduling information t1 through tn.

This eliminates the necessity for switching management, which is necessary for the communication apparatus 1a. Therefore, the communication apparatus 1b
5 can be used for high-speed transfer and is applicable to high-speed communication between general-purpose processors.

Now, a process performed when IP frames include identical frames will be described. Fig. 9 is a view
10 roughly showing a process performed when identical IP frames exist.

In a communication apparatus 10-4, input processing means 11c-1 performs an input process on IP frames and outputs them to frame controlling means 12c. Input
15 processing means 11c-2 performs an input process on integrated frames and outputs them to the frame controlling means 12c.

The frame controlling means 12c transfers IP frame f1a sent from the input processing means 11c-1 and IP frame f1b included in integrated frames sent from the input
20 processing means 11c-2 to output processing means 13c which performs an output process on IP frames. In this case, it is assumed that IP frame f1a and IP frame f1b have the same payload.

25 The output processing means 13c considers IP frame f1a and IP frame f1b to be the same, generates representative frame f2 to which index information

indicating to that effect is added, and transmits it from on data frame line L2a.

This index information includes information that IP frame f1a and IP frame f1b are integrated into one
5 representative frame f2, destinations of IP frame f1a and IP frame f1b, etc.

In a communication apparatus 10-5, input processing means 11d receives representative frame f2, performs an input process on it, and outputs it to frame controlling
10 means 12d.

The frame controlling means 12d divides representative frame f2 sent from the input processing means 11d into IP frame f1a and IP frame f1b on the basis of index information and transfers IP frame f1a to output
15 processing means 13d-1.

Furthermore, the frame controlling means 12d integrates a speech frame sent from input processing means (which performs an input process on speech frames and is not shown) and IP frame f1b into an integrated frame and
20 transfers it to output processing means 13d-2.

The output processing means 13d-1 transmits IP frame f1a onto data frame line L2b. The output processing means 13d-2 transmits an integrated frame including IP frame f1b onto integrated frame line L3b.

25 In the present invention, as described above, when IP frames include identical frames, output processing means generates one representative frame and transmits it onto a

line. Then frame controlling means at the receiving end restores the representative frame to a plurality of identical frames as they were. This enables to reduce the traffic on an interoffice trunk line.

5 A method for integrating speech and data according to the present invention will now be described. Fig. 10 is a flow chart showing the procedure of processes performed in a method for integrating speech and data according to the present invention.

10 [S1] Integrated frames are generated by integrating speech frames, being speech signals made into frames, and data frames, data made into frames.

When integrated frames are generated, speech frames occupy the bandwidth which they use, and the rest of the bandwidth is assigned to data frames. Furthermore, when
15 integrated frames are generated, priority information fields for data frames are created. In that case, high and low priority correspond to connection-mode and connectionless-mode communication respectively. In
20 addition, when integrated frames are generated, an information field for controlling common line signals is created.

 [S2] The input side stores and manages at least one of the three types of frames of speech frames, data frames,
25 and integrated frames. In this case, frames are stored by switching two storage areas every cycle.

 [S3] The routing of speech frames, data frames, and

integrated frames is controlled.

[S4] The output side stores and manages frames transferred, and transmits speech and data frames via a speech and data interface line respectively. Furthermore,
5 the output side transmits integrated frames via an integrated interface line.

In this case, routing control and a switching transfer of frames to the output side are performed on the basis of frame information.

10 Furthermore, on the basis of frame information, routing control is performed and transfer scheduling information is generated. The input side transfers frames to the output side on the basis of the transfer scheduling information.

15 When data frames transferred include identical frames, the output side generates and outputs one representative frame. If a representative frame is received, then a plurality of identical frames are generated at the time of routing control.

20 As described above, a communication apparatus, communication system, and method for integrating speech and data according to the present invention can improve network efficiency by integrating speech and data with a trunk line.

Moreover, the bandwidth ratio of Internet to
25 telephone can be changed dynamically, so line efficiency can be improved. In addition, if all telephone exchanges are equipped with this apparatus, Internet services can be

provided in all areas including depopulated ones.

As described above, a communication apparatus according to the present invention controls the routing of speech frames, data frames, and integrated frames, assigns
5 bandwidth dynamically to lines, and transmits speech frames, data frames, and integrated frames via each line. This enables communication in which speech frames and data frames are integrated efficiently.

Furthermore, a communication system according to
10 the present invention is configured by connecting a communication apparatus to at least one of an office telephone interface line, an office data interface line, and an interoffice trunk line. This will make it easy to perform speech communication, data communication, and
15 speech-data communication in which speech and data are integrated. In addition, this will enable to provide new services with the increase of installations minimized.

Moreover, a method for integrating speech and data according to the present invention controls the routing of
20 speech frames, data frames, and integrated frames, assigns bandwidth dynamically to lines, and transmits speech frames, data frames, and integrated frames via each line. This enables communication in which speech frames and data frames are integrated efficiently.

25 The foregoing is considered as illustrative only of the principles of the present invention. Further, since numerous modifications and changes will readily occur to

those skilled in the art, it is not desired to limit the invention to the exact construction and applications shown and described, and accordingly, all suitable modifications and equivalents may be regarded as falling within the scope
5 of the invention in the appended claims and their equivalents.

10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
2228
2229
2230
2231
2232
2233
2234
22